

VeriFast™ IA Weld Bodies / Pin Styles Quick Reference

No.	VeriFast™ IA Weld Body Style	Insulated Body	Series			Stroke (mm)			Cable Exit Position				Weld Pin Style	Weld Body Foot Print / Other Details
			2	3	4	22	50	69	Top Left	Top Right	Top Middle	Pre-Defined		
1	SXAR (Base Mount) 3.88" (98.43 mm)	X	✓	✓	✓	✓	X	X	✓	✓	X	X		
2	SXKR (Base Mount) 3.88" (98.43 mm) 0.37" (9.40 mm) Contact	✓	✓	✓	✓	X	X	X	X	✓	X			
3	SXTR (Base Mount) 3.88" (98.43 mm) Barbed fitting provided for 1/4" tube	X	✓	✓	✓	X	X	X	X	✓	X			
4	SXQR (Base Mount) 3.88" (98.43 mm) 0.37" (9.40 mm) Contact Barbed fitting provided for 1/4" tube	✓	✓	✓	✓	X	X	X	X	✓	X			
5	SXHR (Base Mount) 3.88" (98.43 mm) Through hole (Ø17/32" clearance hole for 1/2" screw) Barbed fittings provided for 1/4" tube	✓	✓	✓	✓	X	X	✓	✓	X	X			
6	SXJR (Base Mount) 3.88" (98.43 mm) Threaded 1/2"-13 UNC Helicoil Barbed fittings provided for 1/4" tube	✓	✓	✓	✓	X	X	✓	✓	X	X			
7	SXVR (Base Mount) 3.88" (98.43 mm) Barbed fitting provided for 1/4" tube	X	✓	X	X	✓	X	X	X	✓	X			
8	SXWR (Base Mount) 3.88" (98.43 mm) 0.37" (9.40 mm) Contact Barbed fitting provided for 1/4" tube	✓	✓	X	X	✓	X	X	X	✓	X			

✓=Recommended X=Not Available ✓=Available, Not Recommended

VeriFast™ IA Weld Bodies / Pin Styles Quick Reference

No.	VeriFast™ IA Weld Body Style	Insulated Body	Series			Stroke (mm)			Cable Exit Position				Weld Pin Style	Weld Body Foot Print / Other Details
			2	3	4	22	50	69	Top Left	Top Right	Top Middle	Pre-Defined		
9	SXZR (Base Mount) Air Port 10-32 UNF (Barbed fitting provided) 125.30 mm (for Series 2 and 3) 128.52 mm (for Series 4)	X	✓	✓	✓	X	✓	X	X	✓	X			
10	SYVR (Base Mount) 6.77" (172.06 mm)	X	✓	✓	✓	X	✓	X	X	✓	X			
11	SZVR (Base Mount) 7.56" (192.13 mm) (Series 3 and 4 Only)	X	X	✓	✓	X	X	✓	X	✓	X			
12	SXCR (Tapered) 4.63" (117.48 mm) 4.74" (120.52 mm) 5.49" (139.57 mm) (Series 3 only) Electrode Taper = 5 RW Barbed fitting provided for 1/4" tube	X	X	✓	X	✓	X	X	X	X	✓			
13	SXFR (Threaded) 4.63" (117.48 mm) 5.38" (136.53 mm) (Series 3 only) Electrode Thread: 7/8"-14 Barbed fitting provided for 1/4" tube	X	X	✓	X	✓	X	X	X	X	✓			
14	SXGR (Threaded) 4.63" (117.48 mm) 5.38" (136.53 mm) (Series 3 only) Electrode Thread: 7/8"-14 Barbed fitting provided for 1/4" tube	X	X	✓	X	✓	X	X	X	X	✓			
15	Clamp Mount	X	✓	✓	✓	✓	✓	X	X	X	✓			

✓=Recommended X=Not Available ✓=Available, Not Recommended